

KÖSTER KB-Fix 5

Technical guideline / Article number **5.015**
issued: 1st of January 2007 Draft

Fast setting cement for swift installations

Features

KÖSTER KB-Fix 5 is an extremely fast setting waterproof and weatherproof mortar for swift installations.

Field of application

KÖSTER KB-Fix 5 is intended for swift filling of holes and cracks in plaster and masonry, for anchoring wall anchors, anchor fittings, brackets of roof gutters and down pipes, handrails, grates, radiators as well as for swift repairs at home, for sealing pipe feedthroughs; for inside and outside use.

Preparation of substrate

Remove loose particles of plaster and brick, wet holes or respectively cracks with water, put in parts to be anchored.

Application

Mix 3 parts of KÖSTER KB-Fix 5 with 1 part of water into a stiff, viscous mortar. When doing sealing work or when repairing larger areas, press the mortar into place using a board or trowel until it has set.

In cold weather, mix KÖSTER KB-Fix 5 with warm water (approx. 20 °C). KÖSTER KB-Fix 5 can be leaned by adding washed sand and Portland cement (carry out tests before installation).

Consumption

Approx. 1.8 kg / l void

Cleaning of tools

Immediately after use with a lot of water.

Packaging

15 kg bucket

Storage

Store the material in a dry place; in originally sealed containers, it can be stored for approx. 6 months.

Safety precautions

Wear protective gloves and goggles when processing the material.

The accurate and thereby effective and successful application of our products is not subject to our control. The guarantee can therefore only be applied to the quality of our products within the scope of our terms and conditions, not, however, for their effective and successful application. These guidelines replace all previous ones.