

This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

# **Hazardous Substance, NON-Dangerous Goods**

# 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Seal'N'Flex 1

Synonyms:	Mancode
Seal'N'Flex 1 Bahama Beige, 720 grams sausage	217751
Seal'N'Flex 1 Black, 720 grams sausage	217808
Seal'N'Flex 1 Black, 380 grams cartridge	246204
Seal'N'Flex 1 Blue, 360 grams sausage	253707
Seal'N'Flex 1 Bronze, 720 grams sausage	226289
Seal'N'Flex 1 Classic Bone, 720 grams sausage	242322
Seal'N'Flex 1 Classic Bone Exp, 720 grams sausage	366811
Seal'N'Flex 1 Epping Grey, 720 grams sausage	232556
Seal'N'Flex 1 Grey, 720 grams sausage	216275
Seal'N'Flex 1 Grey, 380 grams cartridge	246158
Seal'N'Flex 1 Keystone, 720 grams sausage	251267
Seal'N'Flex 1 Lime Stone, 720 grams sausage	217824
Seal'N'Flex 1 Man Sand, 720 grams sausage	232440
Seal'N'Flex 1 Off White, 720 grams sausage	218626
Seal'N'Flex 1 Redwood, 720 grams sausage	226688
Seal'N'Flex 1 Sand Stone, 720 grams sausage	226203
Seal'N'Flex 1 White, 720 grams sausage	216267
Seal'N'Flex 1 White, 380 grams cartridge	246220
Seal'N'Flex 1 Black (Export), 720 grams sausage	366242
Seal'N'Flex 1 Grey (Export), 720 grams sausage	366145
Seal'N'Flex 1 White (Export), 720 grams sausage	366153

Recommended use: A gunnable, air curing, low modulus 1 part construction sealant.

Supplier: Bostik Australia Pty Ltd Bostik New Zealand Limited

**ABN:** 79 003 893 838

Street Address: 51-71 High Street 19 Eastern Hutt Road

Thomastown VIC 3074 Wingate Lower Hutt

New Zealand

Australia

 Telephone:
 +613 9279-9333
 +644 567-5119

 Facsimile:
 +613 9279-9342
 +644 567-5412

 Website:
 www.bostik.com.au
 www.bostik.co.nz

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 243 622

# 2. HAZARDS IDENTIFICATION

### **AUSTRALIA CLASSIFICATION**

This material is hazardous according to health criteria of Safe Work Australia.

Hazard Category:

Xn Harmful

Risk Phrase(s):

R20: Harmful by inhalation.

R42: May cause sensitisation by inhalation.

Product name: Seal'N'Flex 1 Substance Key: BOS0016402

Issued: 22 December 2009 Version: 2.3 Page: 1 of 7



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

Safety Phrase(s):

S23: Do not breathe vapour.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Poisons Schedule (Aust): Not applicable

### **NEW ZEALAND CLASSIFICATION**

This material is hazardous according to health criteria of ERMA New Zealand

ERMA Group Standard: Construction Products (Subsidiary Hazard) Group Standard 2006; HSR002544

### **HSNO Hazard Classification**

6.1D Substances that are acutely toxic.

6.5A Substances that are respiratory sensitisers

#### **Hazard Statement:**

H332 Harmful If Inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties If Inhaled.

#### **Prevention Statement:**

P102 Keep out of reach of children. P103 Read label before use.

P261 Avoid breathing vapour.

P271 Use only outdoors or in a well-ventilated area.

P285 In case of inadequate ventilation wear respiratory protection

# **DANGEROUS GOODS CLASSIFICATION**

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

# 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Toluene diisocyanate Ingredients determined to be non-hazardous	584-84-9 -	<1.0% Balance
		100%

# 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Product name: Seal'N'Flex 1 Substance Key: BOS0016402

Issued: 22 December 2009 Version: 2.3 Page: 2 of 7



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

**Skin contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically. Effects may be delayed.

# 5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible liquid.

**Fire fighting further advice:** On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

# **6. ACCIDENTAL RELEASE MEASURES**

## **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

#### **LARGE SPILLS**

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable.

# 7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

Product name: Seal'N'Flex 1 Substance Key: BOS0016402

Issued: 22 December 2009 Version: 2.3 Page: 3 of 7



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### National occupational exposure limits:

No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

However for:

	TWA		STEL		CARCINOGEN	NOTICES
	ppm	mg/m3	ppm	mg/m3	CATEGORY	
Isocyanates, all (as -NCO)	-	0.02	_	0.07	-	Sen

As published by the Safe Work Australia or Department of Labour New Zealand.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

WES-TWA (Workplace Exposure Standard – Time-weighted Average). The time-weighted average exposure standard designed to protect the worker for the effects of long-term exposure.

WES-STEL (Workplace Exposure Standard - Short-Term Exposure Limit). The 15-minute average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue changes, or nacosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

- `Sen' notice sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.
- \*\*\* Medical supervision of all employees who handle or come in contact with respiratory sensitisers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products.\*\*\*
- \*\*\* The Occupation Exposure Standards do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further exposure.\*\*\*

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the following ingredients in this material requires Health Surveillance:

Isocyanates.

For detailed information see "Guidelines for Health Surveillance (Safe Work Australia)"

Product name: Seal'N'Flex 1 Substance Key: BOS0016402

Issued: 22 December 2009 Version: 2.3 Page: 4 of 7



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

**Engineering measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

**Personal protection equipment:** OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from polyvinyl alcohol (PVA) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Coloured thixotropic paste with aromatic solvent odour.

N Av Solubility: Specific Gravity (20 °C): 1.26 Relative Vapour Density (air=1): N Av Vapour Pressure (20 °C): N Av Flash Point (°C): 43 (solids) Flammability Limits (%): N Av Autoignition Temperature (°C): N Av Melting Point/Range (°C): N Av **Boiling Point/Range (°C):** N Av pH: N App Total VOC (g/Litre): 64

(Typical values only - consult specification sheet)
N Av = Not available
N App = Not applicable

# 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Avoid high temperatures

Incompatible Materials: Water, alcohols, amines, acids and bases

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes - may include isocyanates.

**Hazardous reactions:** Will react exothermically with water and all organic compounds containing active hydrogen groups.

Product name: Seal'N'Flex 1 Substance Key: BOS0016402

Issued: 22 December 2009 Version: 2.3 Page: 5 of 7



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

Inhalation: Vapours are harmful if inhaled. A respiratory sensitiser. Can cause possible allergic reactions.

Skin contact: Contact with skin may result in irritation.

Eye contact: May be an eye irritant.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Long Term Effects: No information available for product.

# **Acute toxicity / Chronic toxicity**

No LD50 data available for the product.

### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Mobility: No information available.

# 13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

## 14. TRANSPORT INFORMATION

## **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

# **MARINE TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### **AIR TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Product name: Seal'N'Flex 1 Substance Key: BOS0016402

Issued: 22 December 2009 Version: 2.3 Page: 6 of 7



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

# 15. REGULATORY INFORMATION

Poisons Schedule (Aust): Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

# **16. OTHER INFORMATION**

## Literary reference

This Material Safety Data Sheet has been prepared by EIAS Pty Ltd on behalf of its client.

Reason(s) For Issue: Addition to synonyms.

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Seal'N'Flex 1 Substance Key: BOS0016402

Issued: 22 December 2009 Version: 2.3 Page: 7 of 7