



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 21

SDS No. : 460478
V006.0

Teroson AD Adhesive Spray

Revision: 28.03.2017
printing date: 15.04.2019

Replaces version from: 02.05.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Teroson AD Adhesive Spray

Contains:

Methyl acetate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Spray adhesive

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA
Henkelstr. 67
40589 Düsseldorf

Germany

Phone: +49 211 797 0
Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

Supplier: Projex Group Pty Ltd ABN: 13 003 859 916
Street Address: Unit 2/1 Military Road Matraville NSW 2036 Web: www.projex.com.au
Phone #: +612 8336 1666 Fax #: +612 9661 9925 Emergency phone #: Australia +61 432664472

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Aerosols	Category 1
H222 Extremely flammable aerosol.	
Aerosols	Category 3
H229 Pressurised container: May burst if heated.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central Nervous System	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Danger

Hazard statement:

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

**Precautionary statement:
Prevention**

P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P251 Do not pierce or burn, even after use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P211 Do not spray on an open flame or other ignition source.

**Precautionary statement:
Storage**

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Precautionary statement:
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly flammable air/vapor mixtures.

Pregnant women should absolutely avoid inhalation and skin contact.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Spray adhesive

Base substances of preparation:

Styrene-butadiene copolymer
in a mixture of organic solvents
Propellant gas base: propane/butane

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Methyl acetate 79-20-9	201-185-2	20- 40 %	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336
Isobutane 75-28-5	200-857-2 01-2119485395-27	20- 40 %	Flam. Gas 1 H220 Press. Gas
Propane 74-98-6	200-827-9 01-2119486944-21	10- 20 %	Flam. Gas 1 H220 Press. Gas
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	295-763-1 01-2119486291-36	1- < 5 %	Flam. Liq. 2 H225 Asp. Tox. 1 H304 STOT SE 3 H336
Ethyl acetate 141-78-6	205-500-4 01-2119475103-46	1- < 3 %	Flam. Liq. 2 H225 STOT SE 3 H336 Eye Irrit. 2 H319
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	295-763-1 01-2119475514-35	1- < 3 %	Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	300-230-4 01-2119475515-33	1- < 3 %	Asp. Tox. 1 H304 Skin Irrit. 2 H315 Flam. Liq. 2 H225 STOT SE 3; Inhalation H336 Aquatic Chronic 2 H411
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	01-2119475514-35 01-2119484651-34	1- < 3 %	Flam. Liq. 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411
Cyclohexane 110-82-7	203-806-2 01-2119463273-41	0,1- < 1 %	Asp. Tox. 1 H304 STOT SE 3 H336 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Flam. Liq. 2 H225 Skin Irrit. 2

			H315
Butyl hydroxytoluene 128-37-0	204-881-4 01-2119480433-40 01-2119555270-46 01-2119565113-46	0,1- < 1 %	Aquatic Acute 1 H400 Aquatic Chronic 1 H410
n-Hexane 110-54-3	203-777-6 01-2119480412-44	0,1- < 1 %	Flam. Liq. 2 H225 Repr. 2 H361f Asp. Tox. 1 H304 STOT RE 2 H373 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remain (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.

Ingestion:

Rinse mouth, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

Vapors may cause drowsiness and dizziness.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

During processing and drying after adhesion, ventilate well. Avoid all sources of fire such as stoves and ovens. Switch off all electrical devices such as parabolic heaters, hot plates, storage heaters etc. in good time for them to have cooled down before commencing work. Avoid all sparks, including those occurring at electrical switches and devices.

Transport by automobile: leave the container wrapped in a cloth in the trunk, never in the passenger area.

Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, frost-free place.

Storage at 15 to 25°C is recommended.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Spray adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Methyl acetate 79-20-9	200	610	Exposure limit(s):	4 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Methyl acetate 79-20-9			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Isobutane 75-28-5	1.000	2.400	Exposure limit(s):	4	TRGS 900
Isobutane 75-28-5			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Propane 74-98-6	1.000	1.800	Exposure limit(s):	4	TRGS 900
Propane 74-98-6			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Ethyl acetate 141-78-6	400	1.500	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
Ethyl acetate 141-78-6			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):	Indicative	ECLTV
n-Hexane 110-54-3	50	180	Exposure limit(s):	8 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
n-Hexane 110-54-3			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
Cyclohexane 110-82-7 [CYCLOHEXANE]	200	700	Time Weighted Average (TWA):	Indicative	ECLTV
Cyclohexane 110-82-7	200	700	Exposure limit(s):	4	TRGS 900
Cyclohexane 110-82-7			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
2,6-di-tert-Butyl-p-cresol 128-37-0			Short Term Exposure Classification:	Category II: substances with a resorptive effect.	TRGS 900
2,6-di-tert-Butyl-p-cresol 128-37-0		10	Exposure limit(s):	4 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Ethyl acetate 141-78-6	aqua (freshwater)		0,26 mg/l				
Ethyl acetate 141-78-6	aqua (marine water)		0,026 mg/l				
Ethyl acetate 141-78-6	aqua (intermittent releases)		1,65 mg/l				
Ethyl acetate 141-78-6	sewage treatment plant (STP)		650 mg/l				
Ethyl acetate 141-78-6	sediment (freshwater)				1,25 mg/kg		
Ethyl acetate 141-78-6	sediment (marine water)				0,125 mg/kg		
Ethyl acetate 141-78-6	oral				200 mg/kg		
Ethyl acetate 141-78-6	soil				0,24 mg/kg		
Cyclohexane 110-82-7	aqua (freshwater)		0,207 mg/l				
Cyclohexane 110-82-7	aqua (marine water)		0,207 mg/l				
Cyclohexane 110-82-7	aqua (intermittent releases)		0,207 mg/l				
Cyclohexane 110-82-7	sediment (freshwater)				3,627 mg/kg		
Cyclohexane 110-82-7	sediment (marine water)				3,627 mg/kg		
Cyclohexane 110-82-7	soil				2,99 mg/kg		
Cyclohexane 110-82-7	sewage treatment plant (STP)		3,24 mg/l				
2,6-Di-tert-butyl-p-cresol 128-37-0	soil				47,69 µg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	sewage treatment plant (STP)		0,17 mg/l				
2,6-Di-tert-butyl-p-cresol 128-37-0	sediment (freshwater)				99,6 µg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	oral				8,33 mg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (marine water)		0,0199 µg/l				
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (freshwater)		0,199 µg/l				
2,6-Di-tert-butyl-p-cresol 128-37-0	sediment (marine water)				9,96 µg/kg		
2,6-Di-tert-butyl-p-cresol 128-37-0	aqua (intermittent releases)		0,00199 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	dermal	Long term exposure - systemic effects		13964 mg/kg bw/day	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	inhalation	Long term exposure - systemic effects		5306 mg/m3	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	dermal	Long term exposure - systemic effects		1377 mg/kg bw/day	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	inhalation	Long term exposure - systemic effects		1131 mg/m3	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	oral	Long term exposure - systemic effects		1301 mg/kg bw/day	
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - systemic effects		1468 mg/m3	
Ethyl acetate 141-78-6	Workers	inhalation	Acute/short term exposure - local effects		1468 mg/m3	
Ethyl acetate 141-78-6	Workers	dermal	Long term exposure - systemic effects		63 mg/kg	
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - systemic effects		734 mg/m3	
Ethyl acetate 141-78-6	Workers	inhalation	Long term exposure - local effects		734 mg/m3	
Ethyl acetate 141-78-6	General population	Inhalation	Acute/short term exposure - systemic effects		734 mg/m3	
Ethyl acetate 141-78-6	General population	inhalation	Acute/short term exposure - local effects		734 mg/m3	
Ethyl acetate 141-78-6	General population	dermal	Long term exposure - systemic effects		37 mg/kg	
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - systemic effects		367 mg/m3	
Ethyl acetate 141-78-6	General population	oral	Long term exposure - systemic effects		4,5 mg/kg	
Ethyl acetate 141-78-6	General population	inhalation	Long term exposure - local effects		367 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	dermal	Long term exposure - systemic effects		773 mg/kg bw/day	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	inhalation	Long term exposure - systemic effects		2035 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	dermal	Long term exposure - systemic effects		699 mg/kg bw/day	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	inhalation	Long term exposure - systemic effects		608 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	oral	Long term exposure - systemic effects		699 mg/kg bw/day	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	Workers	dermal	Long term exposure - systemic effects		300 mg/kg bw/day	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	Workers	Inhalation	Long term exposure - systemic effects		2085 mg/m3	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	General population	dermal	Long term exposure -		149 mg/kg bw/day	

93924-37-9			systemic effects		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	General population	oral	Long term exposure - systemic effects		149 mg/kg bw/day
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	General population	Inhalation	Long term exposure - systemic effects		447 mg/m3
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	Workers	dermal	Long term exposure - systemic effects		773 mg/kg
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	General population	oral	Long term exposure - systemic effects		699 mg/kg
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	General population	dermal	Long term exposure - systemic effects		699 mg/kg
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	General population	Inhalation	Long term exposure - systemic effects		608 mg/m3
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	Workers	Inhalation	Long term exposure - systemic effects		2035 mg/m3
Cyclohexane 110-82-7	Workers	Inhalation	Acute/short term exposure - local effects		700 mg/m3
Cyclohexane 110-82-7	Workers	Inhalation	Acute/short term exposure - systemic effects		700 mg/m3
Cyclohexane 110-82-7	Workers	Inhalation	Long term exposure - systemic effects		700 mg/m3
Cyclohexane 110-82-7	Workers	Inhalation	Long term exposure - local effects		700 mg/m3
Cyclohexane 110-82-7	Workers	dermal	Long term exposure - systemic effects		2016 mg/kg
Cyclohexane 110-82-7	General population	Inhalation	Acute/short term exposure - systemic effects		412 mg/m3
Cyclohexane 110-82-7	General population	Inhalation	Acute/short term exposure - local effects		412 mg/m3
Cyclohexane 110-82-7	General population	dermal	Long term exposure - systemic effects		1186 mg/kg
Cyclohexane 110-82-7	General population	oral	Long term exposure - systemic effects		59,4 mg/kg
Cyclohexane 110-82-7	General population	Inhalation	Long term exposure - systemic effects		206 mg/m3
Cyclohexane 110-82-7	General population	Inhalation	Long term exposure - local effects		206 mg/m3
Cyclohexane 110-82-7	Workers	dermal	Long term exposure - systemic effects		2016 mg/kg
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m3
2,6-Di-tert-butyl-p-cresol 128-37-0	Workers	dermal	Long term exposure - systemic effects		0,5 mg/kg
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	inhalation	Long term exposure - systemic effects		0,86 mg/m3
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	dermal	Long term exposure - systemic effects		0,25 mg/kg
2,6-Di-tert-butyl-p-cresol 128-37-0	General population	oral	Long term exposure - systemic effects		0,25 mg/kg
n-Hexane 110-54-3	General population	inhalation	Long term exposure - systemic effects		16 mg/m3

n-Hexane 110-54-3	Workers	dermal	Long term exposure - systemic effects		11 mg/kg	
n-Hexane 110-54-3	General population	dermal	Long term exposure - systemic effects		5,3 mg/kg	
n-Hexane 110-54-3	Workers	inhalation	Long term exposure - systemic effects		75 mg/m ³	
n-Hexane 110-54-3	General population	oral	Long term exposure - systemic effects		4 mg/kg	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
n-Hexane 110-54-3	Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone	Urine	Sampling time: End of shift.	5 mg/l	DE BAT		
n-Hexane 110-54-3	Hexane-2,5-dione plus 4,5-Dihydroxy-2-hexanone (with hydrolysis)	Urine	Sampling time: End of shift.	5 mg/l	DE BGW		
Cyclohexane 110-82-7	Total 1,2-Cyclohexane diol	Creatinine in urine	Sampling time: End of shift at end of work week.	170 mg/g	DE BAT		
Cyclohexane 110-82-7	1,2-Cyclohexane diol, with hydrolysis	Creatinine in urine	Sampling time: End of shift at end of work week.	150 mg/g	DE BGW		

8.2. Exposure controls:**Respiratory protection:**

The product should only be used at workplaces with intensive ventilation/extraction. If intensive ventilation/extraction is not possible then self-contained independent respiratory protection should be worn.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from chloroprene rubber are recommended according to EN 374.

Perforation time > 10 minutes

material thickness > 0.6 mm

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	pressurized can liquid colourless
Odor	of solvent
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point (1.013 hPa)	60 °C (140 °F)
Flash point	-30 °C (-22 °F); flash point, Abel-Pensky
Decomposition temperature	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Density (20 °C (68 °F))	0,7 - 0,74 g/cm ³
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Solid content	20,5 - 21,5 %
Oxidising properties	No data available / Not applicable

9.2. Other information

Flow cup viscosity (23 °C (73.4 °F); ; Nozzle: 25 mm)	25 s
--	------

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Temperatures over appr. 50 °C

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

STOT-single exposure:

May cause drowsiness or dizziness.

Inhalative toxicity:

The toxicity of the product is due to its narcotic effect after inhalation.

In the event of protracted or repeated exposure, damage to health cannot be excluded.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye irritation.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methyl acetate 79-20-9	LD50	6.970 mg/kg	oral		rat	not specified
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Ethyl acetate 141-78-6	LD50	6.100 mg/kg	oral		rat	not specified
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 93924-37-9	LD50	> 5.840 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Cyclohexane 110-82-7	LD50	> 5.000 mg/kg	oral		rat	not specified
Butyl hydroxytoluene 128-37-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
n-Hexane 110-54-3	LD50	16.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Isobutane 75-28-5	LC50	260200 ppm	gas	4 h	mouse	not specified
Propane 74-98-6	LC50	> 800000 ppm	gas	15 min	rat	not specified
Ethyl acetate 141-78-6	LC50	200 mg/l		1 h	rat	not specified
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 93924-37-9	LC50	> 23,3 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Cyclohexane 110-82-7	LC50	13,9 mg/l		4 h	rat	not specified
n-Hexane 110-54-3	LC50		vapour	24 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Methyl acetate 79-20-9	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Ethyl acetate 141-78-6	LD50	> 20.000 mg/kg	dermal		rabbit	Draize Test
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	LD50	> 2.920 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
Cyclohexane 110-82-7	LD50	> 2.000 mg/kg	dermal		rabbit	not specified
Butyl hydroxytoluene 128-37-0	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)
n-Hexane 110-54-3	LD50	> 2.000 mg/kg	dermal		rabbit	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methyl acetate 79-20-9	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Ethyl acetate 141-78-6	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Butyl hydroxytoluene 128-37-0	slightly irritating	24 h	rabbit	not specified

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Methyl acetate 79-20-9	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethyl acetate 141-78-6	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Cyclohexane 110-82-7	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butyl hydroxytoluene 128-37-0	slightly irritating		rabbit	Draize Test
n-Hexane 110-54-3	not irritating		rabbit	not specified

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl acetate 141-78-6	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Butyl hydroxytoluene 128-37-0	not sensitising	Draize Test	guinea pig	Draize Test
n-Hexane 110-54-3	not sensitising	Mouse local lymph node assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Methyl acetate 79-20-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobutane 75-28-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isobutane 75-28-5	negative			Drosophila melanogaster	not specified
Propane 74-98-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane 74-98-6	negative			Drosophila melanogaster	not specified
Ethyl acetate 141-78-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Ethyl acetate 141-78-6	negative	oral: gavage		hamster, Chinese	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Cyclohexane 110-82-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
Butyl hydroxytoluene 128-37-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
	negative	in vitro mammalian chromosome aberration test	with and without		not specified
	negative	mammalian cell gene mutation assay	with and without		not specified
Butyl hydroxytoluene 128-37-0	negative	oral: feed		rat	not specified
n-Hexane 110-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
n-Hexane 110-54-3	negative	inhalation: vapour		mouse	not specified
	negative	inhalation: vapour		rat	not specified

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure time Frequency of treatment	Route of application	Method
Butyl hydroxytoluene 128-37-0		rat	male	2 y daily	oral: feed	
n-Hexane 110-54-3		mouse	female	2 y 6 h/d; 5 d/w	inhalation: vapour	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
Ethyl acetate 141-78-6	NOAEL P = 1.500 mg/kg	other inhalation: vapour	94 d	rat	other guideline:
Butyl hydroxytoluene 128-37-0	NOAEL P = 500 mg/kg	Two generation study oral: feed		rat	not specified
n-Hexane 110-54-3	NOAEL P = 9000 ppm NOAEL F1 = 3000 ppm NOAEL F2 = 3000 ppm	Two generation study inhalation: vapour	10 w	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Isobutane 75-28-5		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Propane 74-98-6		inhalation: gas	28 d	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Ethyl acetate 141-78-6	NOAEL=900 mg/kg	oral: gavage	90 ddaily	rat	EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
Ethyl acetate 141-78-6	NOAEL=1,28 mg/l	inhalation	94 dcontinuous	rat	EPA OTS 798.2450 (90-Day Inhalation Toxicity)
Butyl hydroxytoluene 128-37-0	NOAEL=25 mg/kg	oral: feed	daily	rat	not specified
n-Hexane 110-54-3	NOAEL=586 mg/kg	oral: gavage	90 d5 d/w	rat	not specified
n-Hexane 110-54-3	NOAEL=500 ppm	inhalation: vapour	90 d6 h/d; 5 d/w	mouse	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Ecotoxicity:**

Harmful to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Methyl acetate 79-20-9	LC50	250 - 350 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methyl acetate 79-20-9	EC50	1.026,7 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methyl acetate 79-20-9	EC50	> 120 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	> 120 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test) not specified
Methyl acetate 79-20-9	EC10	1.830 mg/l	Bacteria	16 h		
Isobutane 75-28-5	EC50	7,71 mg/l	Algae	96 h		not specified
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	LL50	12 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	EL50	3 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n- hexane 92128-66-0	EL50	55 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEL	30 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethyl acetate 141-78-6	LC50	270 mg/l	Fish	48 h	Leuciscus idus melanotus	DIN 38412-15
Ethyl acetate 141-78-6	EC50	164 mg/l	Daphnia	48 h	Daphnia cucullata	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethyl acetate 141-78-6	EC50	> 2.000 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	2.000 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test) not specified
Ethyl acetate 141-78-6	EC10	2.900 mg/l	Bacteria	18 h		
Ethyl acetate 141-78-6	NOEC	2,4 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	EC50	3 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	NOEC	0,17 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	EC50	3 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	NOEC	0,17 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	LC50	> 1 - 10 mg/l	Fish			OECD Guideline 203 (Fish, Acute Toxicity Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	EC50	3 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute

Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	EC50	> 1 - 10 mg/l	Algae			Immobilisation Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
Cyclohexane 110-82-7	LC50	4,53 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cyclohexane 110-82-7	EC50	0,9 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cyclohexane 110-82-7	EC50	9,317 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	0,94 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) other:	OECD Guideline 201 (Alga, Growth Inhibition Test) not specified
Cyclohexane 110-82-7	IC50	29 mg/l	Bacteria	15 h		
Butyl hydroxytoluene 128-37-0	NOEC	0,053 mg/l	Fish	42 d	Oryzias latipes	OECD Guideline 210 (fish early lite stage toxicity test)
Butyl hydroxytoluene 128-37-0	EC50	0,48 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butyl hydroxytoluene 128-37-0	EC10	0,4 mg/l	Algae	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Butyl hydroxytoluene 128-37-0	NOEC	0,023 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
n-Hexane 110-54-3	LC50	> 1 - 10 mg/l	Fish			OECD Guideline 203 (Fish, Acute Toxicity Test)
n-Hexane 110-54-3	EC50	2,1 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	Algae			OECD Guideline 201 (Alga, Growth Inhibition Test)
n-Hexane 110-54-3	EC 50	> 1 - 10 mg/l	Bacteria			OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
---------------------------------	--------	----------------------	---------------	--------

Methyl acetate 79-20-9		aerobic	> 95 %	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
	readily biodegradable	aerobic	> 70 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	readily biodegradable	aerobic	98 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethyl acetate 141-78-6	readily biodegradable	aerobic	100 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	readily biodegradable	aerobic	98 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	readily biodegradable	aerobic	98 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	readily biodegradable	aerobic	89 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Cyclohexane 110-82-7	readily biodegradable	aerobic	77 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Butyl hydroxytoluene 128-37-0	Not readily biodegradable.	aerobic	4,5 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
	not inherently biodegradable	aerobic	5,2 - 5,6 %	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
n-Hexane 110-54-3	readily biodegradable, but failing 10-day window	aerobic	> 60 %	not specified

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Methyl acetate 79-20-9	0,18					not specified
Isobutane 75-28-5	2,88				20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	3,6				20 °C	other guideline:
Ethyl acetate 141-78-6	0,6					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	4 - 5,7					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Cyclohexane 110-82-7		167		Pimephales promelas		QSAR (Quantitative Structure Activity Relationship)
Cyclohexane 110-82-7	3,44				25 °C	QSAR (Quantitative Structure Activity Relationship)
Butyl hydroxytoluene 128-37-0		330 - 1.800	56 d	Cyprinus carpio		OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
Butyl hydroxytoluene 128-37-0	5,1					other guideline:
n-Hexane 110-54-3	4					not specified

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Isobutane 75-28-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Propane 74-98-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethyl acetate 141-78-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 93924-37-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Naphtha, hydrotreated light, <0,1% benzene 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Cyclohexane 110-82-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butyl hydroxytoluene 128-37-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
n-Hexane 110-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information**14.1. UN number**

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packing group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 79,42 %
(VOCV 814.018 VOC regulation
CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: 2, water-endangering product. (German VwVwS of May 17, 1999)
Classification in conformity with the calculation method

BG regulations, rules, infos: BG data sheet: BGI 621 Solvents
BG regulation: BGV B 1 Handling hazardous substances

Storage class according to TRGS 510: 2B

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.